

H.p. hose reel

RA.AV1100FE

Automatic hose reel, made of painted steel,
inlet G 1/2" M,
outlet G 3/8" M,
200 bar
2900 psi



gr. 20000
oz. 706.0

Automatic hose reel
for hose ϕ 1/2", 20 m-65.60 ft

RA.AV1100

Automatic hose reel, made of stainless steel,
inlet G 1/2" M,
outlet G 3/8" M,
200 bar
2900 psi




Automatic hose reel
for hose ϕ 1/2", 20 m-65.60 ft

gr. 18000
oz. 636.0

ZX.1111

Manual hose reel, made of nylon,
inlet G 3/8" M,
outlet M 22x1,5 M,
200 bar
2900 psi,
150 °C
300 °F



gr. 1300
oz. 45.9

Manual hose reel
for hose ϕ 5/16", 18 m-59.00

RA.ST20FE

Swivel bracket, made of painted steel,
for automatic hose reel
(code RA.AV1100FE)



gr. 1000
oz. 35.0

RA.ST20

Swivel bracket, made of stainless steel,
for automatic hose reel
(code RA.AV1100)



gr. 1000
oz. 35.0

RA.KIT-11

Seal kit,
for automatic hose reel
(codes RA.AV1100FE-RA.AV1100)



gr. 10
oz. 0.4

RA.KIT-92

Spring kit,
for automatic
hose reel
(codes
RA.AV1100FE,
RA.AV1100)



gr. 7850
oz. 277.2

RA.4961

Swivel coupling,
for automatic
painted steel hose reel,
(code RA.AV1100FE)



gr. 240
oz. 8.5

RA.4963

Swivel coupling,
for automatic
stainless steel hose reel,
(code RA.AV1100)



gr. 240
oz. 8.5

Carwash - Swivel couplings

High pressure swivel couplings suitable for high performance in boom carwash systems and also in hose reel. All our swivel couplings are made of brass body with multi-layers coating for anti-corrosion and internal part in SS AISI 316.

Straight swivel couplings



Code	Inlet	Outlet	Weight	Description
CDR.1081	G 1/4" M	G 1/4" F	gr. 330 oz. 11.6	Straight swivel coupling, made of nicked brass, with stainless steel ball bearings lubricated with water resistant grease for low friction. 200 bar-2900 psi, 90°C-195 °F
CDR.1082	G 3/8" M	G 3/8" F	gr. 330 oz. 11.6	
CDR.1083	G 3/8" M	G 1/4" F	gr. 330 oz. 11.6	

90° swivel couplings



Code	Inlet	Outlet	Weight	Description
CDR.1077	G 1/4" M	G 1/4" F	gr. 330 oz. 11.6	90° swivel coupling, made of nicked brass, with stainless steel ball bearings lubricated with water resistant grease for low friction. 150 bar-2000 psi, 90°C-195 °F
CDR.1078	G 3/8" M	G 3/8" F	gr. 330 oz. 11.6	